



IJEAST

INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY



VOLUME : 1 ISSUE : 9 Print / Issue Publication Date: 09-Oct-2016



ISSN : 2455-2143



Indexed In



WWW.IJEAST.COM

editor@ijeast.com



MULTIOBJECTIVE OPTIMIZATION OF CRANKSHAFT PIN GRINDING

Vinod Hange

Student of Master of Mechanical Engineering
MGM College of Engineering
Aurangabad, Maharashtra

Dilip Khedekar

Faculty of Mechanical Engineering,
MGM College of Engineering
Aurangabad, Maharashtra

Abstract: The Crankshaft grinding is the most critical process in the manufacturing of crankshaft. After induction hardening the pins needs to be grind cylindrically using micromatic machine. Being the sensitive and very precise process chances of rejection and rework is high. So it is important to optimize the process. Every process has some input and some output, like wise here we have taken machine input parameter which are having great influence on quality of grinding they are Work Speed, Cutting Speed, Feed rate, Dressing feed rate and Dressing depth of cut. Similarly at output we have taken objectives to be optimized as-Surface Finish, Ovality and Chatter Marks. For Multiobjective Optimization technique Grey Relational Analysis is used.

Keywords-Work Speed, Cutting Speed, Feed rate, Dressing Feed rate, Dressing depth of cut, Surface finish, Ovality, Chatter Marks

I. INTRODUCTION

Grinding as defined by Webster's dictionary as "To reduce to small fragments by friction", but this type of material removal process is not small in a commercial sense, as it is a billion dollar growth industry that accounts for approximately 25% of all machining operations in manufacturing. Grinding has traditionally been one of the few manufacturing operations to be least understood, with production grinding problems being treated more like black magic, and relying on the experience of the operator, then using scientific principles. This is particularly in case for crankshaft pin grinding, where little research has been conducted to understand the process. There are many variables in the crankshaft pin grinding process that need to be studied as a complete system. Incorrect grinding can contribute to unsightly side effects, such as burn, poor quality surface finish and part sizing problems. The rejection rate of crankshafts directly associated with the

grinding of the crankshaft pins at the manufacturer was approximately one out of every fifty crankshafts.

These problems, if left unsolved had been noted to cause engine seize up, high engine oil usage, vibrations and knocking sounds within the engine. Thus the crankshafts are usually unusable or required time and money to rectify the problem, and hence an experimental study into the variables that affects the end quality of the crankshaft pin grinding process was required to prevent these quality and other problems from occurring. In crankshaft manufacturing process, after induction hardening no other process is feasible to have close tolerances of pin and journal surfaces that are obtained. Grinding being one of the final operations in crankshaft manufacturing, with less tolerance zone within which the jobs must be produced. The defects found such as chatter marks, ovality, taper, radius dimensions, surface finish, geometric errors and surface burn, because of which jobs are mostly rejected during grinding. Once it is rejected we cannot rework it. So there is a huge loss of time, cost, man-hours, material, profit etc. Hence the process need to be studied and should be optimized so that the jobs produced will be within tolerance zone and can reduce the losses during manufacturing.

II. METHODOLOGY AND EXPERIMENTATION

A set of experiments were conducted on Micromatic Cylindrical Grinding Machine on 38MnVS6 steel material to determine effect of machining parameters namely work speed, cutting speed, feed rate, dressing feed rate and dressing depth of cut. For three levels and five factors L27 Orthogonal array is selected for carrying experiment using design of experiments (DOE) and relevant ranges of parameters are decided based on experience and specification

Specified of machine. Grinding wheel used for the present work is the aluminum oxide abrasive with vitrified bond with constant speed of 1350 RPM and water miscible coolant (Lavish) was supplied in all grinding experiments.



The jobs have undergone turning and hardening processes before grinding. Hardening is done for better output response and the BHN is maintained at the range of 30-40 BHN.

Table1. For Process Parameter and their Levels-

S. No	Parameter	Units	Sym bol	Low	Mediu m	High
1	Work speed	rpm	A	40	50	60
2	Cutting speed	m/min	B	35	40	45
3	Feed Rate	mm/Sec	C	0.01	0.15	0.30
4	Dressing Feed Rate	mm/Sec	D	0.120	0.150	0.180
5	Dressing Depth of Cut	mm	E	0.035	0.040	0.040

For Output-

1. These chatter marks are measured in terms of marks per unit inch area.
2. Ovality is measured by snap gauge with dial indicator manually and by air gauges (Etamic) systems in microns.
3. Surface roughness is measured by Taylor Hobson surface profiler& units in microns

Observation Table (Used L27 Array)

Step-I: Arranging an Orthogonal Array & Corresponding								
1	2	3	4	5	6	7	8	9
Exp	Input Parameters					Output Parameters		
	Work Speed (rpm)	Cutti ng Speed	Feed Rate	Dress ing Feed Rate	Dress ing Depth of Cut	Chatt er Marks (mm /Inche s)	Ovality (micron s)	Surface Rough ness in Micron s (Ra)
1	40	35	0.1	0.12	0.03	7.5	9	0.2
2	40	35	0.1	0.12	0.04	7.5	9	0.2
3	40	35	0.1	0.12	0.04	6.5	9	0.3
4	40	40	0.15	0.15	0.03	6.5	8.5	0.3
5	40	40	0.15	0.15	0.04	8.5	8.5	0.3
6	40	40	0.15	0.15	0.04	7.5	8.5	0.4
7	40	45	0.3	0.18	0.03	8.5	9.5	0.3

8	40	45	0.3	0.18	0.04	7.5	9.5	0.3
9	40	45	0.3	0.18	0.04	8.5	9.5	0.3
10	50	35	0.15	0.18	0.03	15	5.5	0.3
11	50	35	0.15	0.18	0.04	14	4.5	0.4
12	50	35	0.15	0.18	0.04	15.5	5.5	0.3
13	50	40	0.3	0.12	0.03	13.5	5.5	0.4
14	50	40	0.3	0.12	0.04	14.5	5.5	0.4
15	50	40	0.3	0.12	0.04	14.5	4.5	0.4
16	50	45	0.1	0.15	0.03	15	4.5	0.5
17	50	45	0.1	0.15	0.04	14.5	4.5	0.5
18	50	45	0.1	0.15	0.04	15.5	3.5	0.6
19	60	35	0.3	0.15	0.03	8.5	11.5	0.7
20	60	35	0.3	0.15	0.04	7.5	10.5	0.7
21	60	35	0.3	0.15	0.04	7.5	10.5	0.7
22	60	40	0.1	0.18	0.03	7	11.5	0.8
23	60	40	0.1	0.18	0.04	7	12.5	0.8
24	60	40	0.1	0.18	0.04	8	11.5	0.7
25	60	45	0.15	0.12	0.03	5.5	11.5	0.7
26	60	45	0.15	0.12	0.04	7.5	11.5	0.8
27	60	45	0.15	0.12	0.04	7.5	11	0.8

In GRA, data pre-processing is required since the range and unit in one data sequence may differ from the others. Data pre-processing is also necessary when the sequence scatter range is too large, or when the directions of the target in the sequence are different.

III. INDENTATIONS AND EQUATIONS

Step -2 Pre- Processing Data For Analysis			
	Chatter Marks	Ovality	Surface Roughness
For Experiment No	7	8	9
Max Value	15.5	12.5	0.8
Min Value	5.5	4.5	0.2



By considering Lower is Best and using the formula to calculate Maximum & Minimum value-

Formula Used- $x = (\text{Max} - \text{Current Value}) / \text{Max} - \text{Min}$

1	2	3	4
Experiment No	Chatter Marks (mm/Inches)	Ovality (microns)	Surface Roughness in Microns (Ra)

Table- Altered Values			
1	2	3	4
Experiment No	Chatter Marks(mm/Inches)	Ovality (micron)	Surface Roughness in Microns (Ra)
1	0.8	0.4375	0.966667
2	0.8	0.4375	0.975
3	0.9	0.4375	0.85
4	0.9	0.5	0.9
5	0.7	0.5	0.825
6	0.8	0.5	0.716667
7	0.7	0.375	0.808333
8	0.8	0.375	0.816667
9	0.7	0.375	0.808333
10	0.05	0.875	0.791667
11	0.15	1	0.7
12	0	0.875	0.791667
13	0.2	0.875	0.666667
14	0.1	0.875	0.625
15	0.1	1	0.616667
16	0.05	1	0.525
17	0.1	1	0.516667
18	0	1.125	0.258333
19	0.7	0.125	0.158333
20	0.8	0.25	0.15
21	0.8	0.25	0.141667
22	0.85	0.125	0.05
23	0.85	0	0.025
24	0.75	0.125	0.158333
25	1	0.125	0.166667
26	0.8	0.125	0
27	0.8	0.1875	-0.00833

Ref. Seq	1	1	1
1	0.2	0.5625	0.033333
2	0.2	0.5625	0.025
3	0.1	0.5625	0.15
4	0.1	0.5	0.1
5	0.3	0.5	0.175
6	0.2	0.5	0.283333
7	0.3	0.625	0.191667
8	0.2	0.625	0.183333
9	0.3	0.625	0.191667
10	0.95	0.125	0.208333
11	0.85	0	0.3
12	1	0.125	0.208333
13	0.8	0.125	0.333333
14	0.9	0.125	0.375
15	0.9	0	0.383333
16	0.95	0	0.475
17	0.9	0	0.483333
18	1	-0.125	0.741667
19	0.3	0.875	0.841667
20	0.2	0.75	0.85
21	0.2	0.75	0.858333
22	0.15	0.875	0.95
23	0.15	1	0.975
24	0.25	0.875	0.841667
25	0	0.875	0.833333
26	0.2	0.875	1
27	0.2	0.8125	1.008333

Step-4 Calculating Gray Coefficients $\zeta_i(k) = \frac{\Delta_{\min} + \zeta \Delta_{\max}}{\Delta_{oi} + \zeta \Delta_{\max}}$

Table For Grey Relation Coefficient

Step-3 As we are Giving Equal weighting for all output so considering 1 as a reference sequence

Table obtained after assigning reference sequence factor for each reading

1	2	3	4
Experiment No	Chatter Marks (mm/Inches)	Ovality (microns)	Surface Roughness in Microns (Ra)
1	0.714285714	0.4705882	0.9375



2	0.714285714	0.4705882	0.952381	6	0.617527862
3	0.833333333	0.4705882	0.769231	7	0.597445337
4	0.833333333	0.5	0.833333	8	0.630145825
5	0.625	0.5	0.740741	9	0.597445337
6	0.714285714	0.5	0.638298	10	0.616903313
7	0.625	0.4444444	0.722892	11	0.665123457
8	0.714285714	0.4444444	0.731707	12	0.613071895
9	0.625	0.4444444	0.722892	13	0.594871795
10	0.344827586	0.8	0.705882	14	0.576190476
11	0.37037037	1	0.625	15	0.641060198
12	0.333333333	0.8	0.705882	16	0.619216033
13	0.384615385	0.8	0.6	17	0.621872478
14	0.357142857	0.8	0.571429	18	0.689783743
15	0.357142857	1	0.566038	19	0.453769057
16	0.344827586	1	0.512821	20	0.494885362
17	0.357142857	1	0.508475	21	0.494127958
18	0.333333333	1.3333333	0.402685	22	0.492564906
19	0.625	0.3636364	0.372671	23	0.480515718
20	0.714285714	0.4	0.37037	24	0.467657946
21	0.714285714	0.4	0.368098	25	0.579545455
22	0.769230769	0.3636364	0.344828	26	0.47041847
23	0.769230769	0.3333333	0.338983	27	0.475576603
24	0.666666667	0.3636364	0.372671		
25	1	0.3636364	0.375		
26	0.714285714	0.3636364	0.333333		
27	0.714285714	0.3809524	0.331492		

Step-6 Observing Highest Value in Above Table & Assign Rank

Step-5 Calculating Grey Relational Grade

Formula= $\frac{1}{3}$ (Values of Column (2+3+4))-By applying Gray Relation Analysis

1	2
Experiment No	Grey Relation Grade
1	0.707457983
2	0.712418301
3	0.691050779
4	0.722222222
5	0.62191358

1	2	3
Experiment No	Grey Relation Grade	Rank
1	0.707457983	3
2	0.712418301	2
4	0.722222222	1

We can observe that the Highest Value is obtained at Experiment 4 Hence we are getting optimum results for three output.



1	2	3	4	5	6	7	8	9	
Experiment No	Level of Parameters					Chatter Marks (mm/Inches)	Ovality (microns)	Surface Roughness in Microns (Ra)	
	Work Speed (rpm)	Cutting Speed	Feed Rate	Dressing Feed Rate	Dressing Depth of Cut				
4	40	40	0.15	0.15	0.035	6.5	8.5	0.26	Calculated
Actual Obtained Values	40	40	0.15	0.15	0.035	6.23	8.01	0.27	From Trial Practical Values Obtained
						4.153846	5.764706	3.846154	% Error

IV. CONCLUSION

From above all calculations & results obtained we can conclude that, to optimize the multi objective of an experiment or trial the gray regression analysis is very useful method. In Crankshaft grinding optimization we got optimum results of chatter mark 6.5 mm/inches, ovality 8.5 microns & Surface roughness 0.26microns when if we used at input Work Speed 40 rpm, Cutting Speed 40, Feed rate 0.15, Dressing Feed rate 0.15 & Dressing depth of cut 0.035.

V. REFERENCES

Journal Papers:

1 Determination and Optimization of Chatter, Ovality & Surface Roughness in Crankshaft Grinding Process by Using Taguchi Method of Analysis. by Vinod Hangel, Bharat Shirke², Munjabadas Kadam³, D.Khedekar⁴ and M.V.Kawade(IJAST) ISSN 2229 5216

2 Coverdale, Stephan Roger, "Finer tolerances demand better measurement methods; identify chatter marks on crankshaft and camshaft with confidence. (QUALITY MEASUREMENT)" Published in- US 6767273 B1 published on [27-Jul-2004](#).

3 I. Inasak, B. Karpuschewski, H. S. Lee, Grinding Chatter- origin and suppression. Published: CIRP Annals-Manufacturing Technology, Volume 50, Issue 2, 2001.

4 Robert, Woodbury. History of the Grinding Machine. 2nd. Cambridge: M.I.T. Press.

5 S. Malkin, C. Geo et al, Simulation, Optimization and Control of Cylindrical Grinding Processes. Publication-cnki: ISSN: 1006-852X.0.2001-05-002.

6 Wu, Ganghua He, Yongyi Shen, Nanyan Tian, Yingzhong Li, Wei, Crankpin non-circular grinding progress error forecast and compensation based on RBF-NN. Publication: [Technology and Innovation Conference, 2006. ITIC 2006. International](#). Issue Date: 6-7 Nov. 2006.

7 Berend Denkena, Niklas Kramer, Monitoring of Roundness Errors in Continues Path Controlled Crankshaft grinding process. Publication- IPMT, Hannover University, Germany.

8 W. J. Whitney Jr., B.E. Schwab, Crankshaft surfaces: Finishing methods, surface characterization and Their Influence on wear. Publication- Wear, Volume 108, Issue 4, 15 April 1986, Pages 345–356 (Elsevier Publications).

9 T. Fujiwara, Shinya Tsukamoto, M. Miyagawa, Analysis of the Grinding Mechanism with Wheel Head Oscillating Type CNC Crankshaft Pin Grinder. Publication-Key Engineering Materials (Volumes 291- 292).

IJEAST

INTERNATIONAL JOURNAL OF ENGINEERING APPLIED SCIENCE AND TECHNOLOGY



AUTHORS

 Vinod Hange

 Dilip Khedekar



ABOUT IJEAST

International journal of Engineering Applied Science and Technology (IJEAST) is a peer-reviewed, open access journal that publishes high - quality research paper in the field of Engineering, Applied Science and Technology.

IJEAST aims to provide a platform for researchers, academicians, and professionals to share their innovative ideas, research findings, and practical experiences with the global scientific community.

JOURNAL METRICS

H

H-INDEX

33

i10

i10-INDEX

154

“

IJEAST
CITATIONS

9,647

(IJEAST CITATIONS)



PEER-REVIEWED
& OPEN ACCESS

PUBLISHED
MONTHLY



PEER REVIEWED

All submission are rigorously peer reviewed to ensure quality.



AUTHORS ARE OUR PRIORITY

We value our authors and recognize their contribution to the advancement of research and knowledge.



OPEN ACCESS

Free and unrestricted access to research for all.



GLOBAL REACH

Connecting researchers and professionals worldwide.



TIMELY PUBLICATION

We ensure a swift and efficient publication process.



For more information, visit our website
www.ijeast.com



editor@ijeast.com



www.ijeast.com



India



2455-2143