



IJEAST

INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY



VOLUME : 4 ISSUE : 06 Print / Issue Publication Date: 06-Dec-2019



ISSN : 2455-2143



DOI : 10.33564/IJEAST.2019.v04i06.053

Indexed In



WWW.IJEAST.COM

editor@ijeast.com



DESIGN AND DEVELOPMENT OF SCR SYSTEM FOR NOX REDUCTION BY USING VARIOUS CATALYSTS

Mr. Raju B Tirpude
 Lecturer
 Automobile Engineering
 Department
 Government
 Polytechnic, Nagpur

Dr. S.W. Rajurkar
 Dept. of Mech. Engg.
 Government
 Engineering, College,
 Chandrapur

Dr. G.K. Awari
 Head of Automobile
 Engineering
 Department
 Government
 Polytechnic, Nagpur

Mr. Ashish M.
 Wankhede
 Lecturer
 Automobile Engineering
 Department
 Government
 Polytechnic, Nagpur

Abstract - Diesel engines are generally used in many areas like automobile industry, locomotive industry, power generation etc. due to its high break power output and thermal efficiency. An oxide of nitrogen (NO_x) is one of the most hazardous pollutants which come out from diesel IC engine through tail pipe. Emission of nitrogen oxide (NO_x) contribute significantly to our environment, which is a savior environmental problem of NO_x which reacts with in the air to form nitric acid (HNO₃), contributing to soil eruption and water acidification in sensitive and metropolitan areas. Various present technologies available for NO_x reduction either increases other polluting gas emission on increase fuel consumption in an IC engine. Selective catalyst reduction systems (SCR) are the most effective and commonly used post combustion NO_x reduction processes available in automobile and power generation sector. SCR utilizes a chemical reaction where vaporized ammonia (NH₃) is collected from the mixture of Urea and distilled water. Various catalysts are injected into the exhaust gases. The prime objective is to convert nitrogen oxide (NO_x) to nitrogen (N₂) and water (H₂O). The existing SCR system is a modified by adding some of the component and use various catalysts injected in tail pipe through feed pump. It has been observed that the NO_x is reduced due to new SCR system. This process is called as deNO_xtation process. In this SCR system denotation level has been reduced, and also contribute to reducing NO_x by 65 to 70%.

Keywords – Exhaust gas emission, Diesel emission control system; advance SCR, Urea, Catalyst, Ammonia (NH₃)

I. INTRODUCTION

As per Honorable Supreme Court decision the emission norms in India will be changed with effect from the year of 2020 as given below.

stage	date	CO	HC	HC+NO _x	PM
Gram/km					
Compression ignition (diesel engine)					
BS IV	2010	0.5	-	0.3	0.025
BS VI	2020	0.5	-	0.17	0.0045
Euro 6	2014	0.5	-	0.17	0.005
Spark ignition (petrol engine)					
Bs IV	2010	1	0.1	0.08	-
Bs VI	2020	1	0.1	0.06	0.0045
Euro 6	2014	1	0.1	0.06	0.005

Table No: 1.1 emission norms

A EURO-VI norm has the stringent limits of emission standards legislation, Selective Catalytic Reduction (SCR) technology has been used in automobile sector. The maximum NO_x conversion efficiency of SCR depends upon temperature and mass flow rate (m_f) of an exhaust gas emission. Nowadays the necessity for the SCR technology is continuously increasing due to the fact that the emission legislation has been expanded into the non-road market. To convert nitrogen oxides (NO_x) the nitrogen (N₂) and water (H₂O) separation is the main objective of this distinct SCR technology system which is more efficient than existing SCR systems. The key is to reform the chemical reaction that is called as deNO_xtation process.

Ammonia (NH₃) or urea (NH₂-CO-NH₂) is used as reducing agent in SCR system. When urea and distilled water combined as a mixture, then formation of ammonia (NH₃) which is injected in tail pipe through feed pump. Automobile manufactures focused their attention towards the further improvement of the technique to make it suitable for




automobiles having diesel engines. Reduction of catalytic converter volume at low temperatures and the suitable dosing strategy for NH₃ at frequently on diesel engines with the help of digital exhaust gas analyzer involved with modified SCR systems. Additionally, the risk associated concerning storing and handling of gaseous NH₃ is significant. It is not commonly used as a reducing agent directly because; ammonia is very toxic in nature. For reasons of toxic nature of NH₃ and handling and storing problems, urea is the preferred substitute for NH₃ as a reducing agent in automotive applications. [1]

The major pollutant emissions of the diesel engines are NO_x, particulate matters, and smoke and soot particles. Although all other emissions, NO_x is one of the most important emission from diesel engine. It plays an important role in the atmospheric ozone depletion and global warming. It is also most precursors to the photochemical smog. Component of smog irritate eyes and throat, stir up asthmatic attacks, decrease visibility and damages plants life as well as human life and materials as well. By dissolving with water vapors NO_x from acid rain which has direct and indirect affects environmental aspects. [9]

This distinct SCR technology permits the NO_x reduction reaction to take place in an oxidizing atmosphere. It is called selective because the catalytic reduction of NO_x with ammonia(NH₃), urea, monomethylamine, di-methylamine, try methylamine, cyanuric acid, carbonates, ammonium carbonate, ammonium bicarbonate, etc.. SCR is a process for reducing the concentration of NO_x from the combustion exhaust, which involves the injection of aqueous solution of urea in the tail pipe of a four stroke. [9]

Urea has been selected for reluctant in most of the applications, stored on board in an aqueous solution. To overcome the difficulties associated with pure ammonia, urea is selected. Urea can be hydrolyzed and decomposed to generate ammonia (NH₃). An injected aqueous solution of urea solution is decomposed into ammonia and water vapour, and then decomposed ammonia reacts with oxides of nitrogen and reduced into eco-friendly nitrogen (N₂) and water vapor.

Following chemical reactions are prominent in new design of SCR system.



The concept of using urea in modified SCR systems for the reduction of NO_x emissions in diesel engines. Since then, many applications have been developed, some of which have reached commercially. But, it is still a challenge for researchers.

II. LITERATURE SURVEY

Urea –SCR, the selective catalytic reduction using urea as reducing agent has been investigated for about 10 years in detail and today is a well-established technique for DeNO_x of stationary diesel engines. The paper discusses the fundamental problems and challenges if urea-SCR is extended to mobile applications. [1]

Choice of catalyst types to reduce the NO_x emissions down to Euro V level. A novel urea injection system is also presented, which is based on a mass produced dosing pump that is combined with an electronic control unit. The results indicated that it is possible to have a NO_x conversion above 80% with ammonia slip below 10ppm using 30 liters of urea on 130 cpsi catalysts for a 12 cylinder diesel engine. [2]

Selective Catalytic Reduction technology is being applied for controlling emissions on oxides of nitrogen from coal-fired boilers. The vanadium and titanium oxides, used commonly in the vandia-titania SCR catalyst for NO_x reduction. [3]

Injection of aqueous solutions of urea in the exhaust for the reduction of NO_x in a single cylinder light duty DI diesel engine. Several kinds of concentration of urea solution varying from 10 to 40% by weight with different flow rates of urea solution varying from 250ml/hr to 750ml/hr were tested by fitting vanadium as catalyst which improved the chemical reactions even at a lower temperature of 190°C. Results showed that a maximum of 27.46% of NO_x reduction was achieved with an optimised flow rate of 0.75lit/hr with 10% urea concentration. [4]

The performance, combustion and emission characteristics on CI engine fuelled with cotton seed oil blends of 25%, 50% 75% and 100% in volume. Due to increase of oxides of nitrogen compared to neat diesel, the Selective catalytic Reduction system was implemented in exhaust pipe. The results indicated that the amount of oxides of nitrogen was decreased rapidly on injection of 30% concentration of urea solution. [5]

The injection of aqueous solutions of urea in the tail pipe of a diesel engine. Four observations were made for the exhaust emission NO_x analysis of concentration of urea solution 0 to 30% by weight with different flow rates of urea solution as reluctant by fitting marine ferromanganese nodule as SCR catalyst. It was observed that 64% of NO_x reduction was achieved. [6]

The use to fully understand the impacts of biodiesel on the diesel engine combustion process and pollutant formation. This paper is more concerned with an experimental investigation to study the diesel engine emission characteristics using Mahua biodiesel with the help of a Three Way Catalytic converter with Diesel Exhaust Fluid (DEF) by running the engine. Almost 90% NO_x emissions got reduced and the emission values recorded were much less when



compared to Bharat stage- IV Norms for selected engine at all operated loads with retrofit arranged.^[7]

Pongamia pinata methyl ester (PPME) chosen as an alternative fuel for diesel engines. Injection of aqueous solutions of urea in the tail pipe of a diesel engine fuelled with Pongamia pinata methyl ester (PPME) for the reduction of oxides of nitrogen (NO). Four observations were made for various concentration of urea solution 0%, 10%, 20%, and 30% by weight with different flow rates of urea solution as reductant by fitting Marine Ferromanganese nodule as SCR catalyst which improves the chemical reactions. 64% NO_x reduction achieved with the urea flow rate 0.60 lit/hr, 30% concentration of urea solution and marine ferromanganese nodule as SCR.^[8]

Selective Catalytic Reduction (SCR) technique of reduction of NO_x is most suitable for automobile diesel engines to meet the upcoming stringent emission norms. Direct measurement of ammonia storage may increase opportunities for significant improvement. Although the technology is more efficient, there are several drawbacks like ammonia slip, deposit formation, etc. that are associated with it. It requires up gradation of technology. In order to avoid these problems mixers are most commonly used in SCR systems.^[9]

The characteristics of the element technology of the SCR system had been ascertained, SCR catalyst is added that combined the entire element in single converter. This effort successfully identified specification that enhances NO_x conversion performance while finding a balance with soot combustion performance & pressure loss characteristics.^[10]

Performance is validated by measuring gas composition as well as NO_x conversion across a downstream SCR substrate unit. The use of gaseous NH₃ also allow for greater NO_x conversion efficiency without deposit formation.^[11]

While comparing the optimal SCR performance with one and two injectors for two different application with split SCR catalyst, the global optimal dosing control were found in using dynamic programming and the resulting NO_x & NH₃ emissions from those control were compared to quantify possible benefits from the added degree of freedom provided by the second injector.^[12]

Relevant to model based control design for a Urea based Selective Catalytic Reduction (SCR) process relevant to automotive applications. A three state, control oriented, lumped parameter model of the system is used to investigate essential controllability and observability properties of the Urea-SCR plant. Results from the controllability and observability analysis of both nonlinear and linearized models are shown to have realistic implications. Observer design for predicting gas phase ammonia slip is outlined and results presented. An altered definition of the catalyst efficiency is used in control design.^[13]

The urea decomposition process in diesel exhaust gas was elucidated. Several kinds of urea decomposition catalysts

were investigated and the material which showed the best performance in NH₃ (ammonia) formation was used to improve the low temperature performance of Cu-zeolite catalysts.^[14]

The method of reducing the amount of NH₃ slip was investigated. It is well known that the amount of ammonia slip after the Urea-SCR system must be under 10 ppm and therefore materials with lower NH₃ slip are preferred. The smaller the amount of NH₃ slip, the larger the amount of urea that can be injected into the system and this leads to higher NO_x conversion.^[15]

Net soot burn was observed for the 2010 CSF system when operating with standard EGR at the specific conditions chosen for these series of testing. The high passive filter regeneration activity of the SCR-DPF system with the engine operating at high engine-out NO_x may result in less frequent active regeneration events and, hence, reduce the fuel penalty associated with active regeneration. The results of this work demonstrated that using SCR-DPF systems not only could meet current NO_x reduction regulations but also improve fuel economy for heavy duty diesel vehicles by allowing them to operate at higher engine out NO_x conditions.^[16]

It is demonstrated that such approach is capable of providing enough ammonia not only for small diesel engines, but also for those within typical light and medium duty applications. A pick-up truck demonstration illustrates the initial feasibility of such a system to generate and dose ammonia throughout transient duty cycles; however, much effort is necessary to develop the system for serial production, further proving the many other suggested benefits. Interestingly, the demonstrated results did not require engine modifications, suggesting an option as a Bolton solution for NO_x abatement retrofits, necessitating less packaging than an equivalent liquid urea SCR system.^[17]

Selective Catalytic Reduction (SCR) catalysts have been demonstrated as an effective solution for controlling NO_x emissions from diesel engines. There is a drive to reduce the overall packaging volume of the after treatment system for these applications. In addition, more active SCR catalysts will be needed as the applications become more challenging: e.g. lower temperatures and higher engine out NO_x, for fuel consumption improvements. One approach to meet the challenges of reduced volume and/or higher NO_x reduction is to increase the active site density of the SCR catalyst by coating higher amount of SCR catalyst on high porosity substrates (HPS). This approach could enable the reduction of the overall packaging volume while maintaining similar NO_x conversion as compared to 2010/2013 systems, or improve the NO_x reduction performance for equivalent volume and NH₃ slip. In this work, systems consisting of SCR coated on high porosity substrates were evaluated in comparison to standard substrate based SCR systems used in typical 2010 applications.^[18]

Many of the researchers have attempted to preside the solution to NO_x emission from the CI engine, but no

researcher has provided the efficient design of SCR system using urea solution. An attempt has been made in this research work to design completely new SCR system to reduce the level of NO_x emission from the engine. Following table refers to the pollution board of India for BS-IV norms.

Standard	Test Cycles	CO	HC	NO _x	PM
		g/kWh			
BS IV	European Steady-state Cycle (ESC)	1.5	0.46	3.50	0.02
	European Transient Cycle (ETC)	4.0	0.55	3.50	0.03

Table No. 2: emission norms




Figure No -1: NO_x emission standard according to EURO Standards^[10]

III. EXPERIMENTAL SETUP

New SCR system consists of 2 catalytic converter instead of single catalytic converter. Two catalytic converter arranged in a series connection in order to reduce the NO_x emission as shown in experimental block diagram. Pulse width module electronics circuit is used to control the injection timing. In this circuit, in-built RC timer circuit is used.

Injector (solenoid type valve) is used to create high pressure in pump and to inject the aqueous ammonia in tail pipe. Injection system is fixed between the two catalytic converter for injection purpose. High pressure feed pump is attached with high pressure pipe to supply urea solution through injection system and all the setup connected to the DC battery. Experimental setup is shown in figure no 2.




Figure 2: block diagram of New SCR System



Figure 3: DeNOxation injection system




Figure 4: Catalytic converter connected in series for New SCR




Figure 5: Modified SCR System

IV. METHODOLOGY & EXPERIMENTATION


Before starting the engine, urea solution is to be prepared for different concentration varying with 20grams, 30grams and 40grams by weight along with 1litre of distilled water. Also we make sure that all the connection of control circuit board should be properly enact. The modified SCR should be soot free & properly functioning. Before starting the operation of the setup is replaced by the new SCR with modified SCR system in diesel vehicle.

Following readings are recorded with the help of flue gas analyzer

- 20gm of urea/ lit of distilled water**
 NO_x = **1.20 PPM** (Part per million)



- 30gm of urea/ lit of distilled water**
 NO_x = **0.90 PPM** (Part per million)



- 40gm of urea/ lit of distilled water**
 NO_x = **0.65 PPM** (Part per million)



The properly calibrated instruments are used for the measurement of the exhaust gas emission. the calibration is done with the help of standard procedure.

Following exhaust gas analyser is used for the research work.

Conc. of urea solution	NO _x	CO
10g/lit of distilled water	1.36ppm	0.76ppm
20g/lit of distilled water	1.20ppm	0.27ppm
30g/lit of distilled water	0.90ppm	0.24ppm
40g/lit of distilled water	0.65ppm	0.21ppm
50g/lit of distilled water	0.46ppm	0.19ppm

Table No 4: emission norms

The experimentation was conducted on no load condition on the following CI engine.

Engine Specification (CI)


Test bed	330kw,AVL transient dynamometer
Engine specification	6 cylinder ,inline common rail
Bore	103mm
Stroke	114mm
Gas analyzer	NO _x ,Co,HC,raw gas analyzer
NH ₃ measurement	AVL –FTIR
In cylinder pressure measurement	AVL smart sampler
SCR catalyst	5.66”X7.5” ,400cpsi

Table No 4: emission norms




V. RESULTS AND DISCUSSIONS

The output obtained from the experiment is plotted to determine the effect of the injection of urea solution at various concentration and to obtain the value of corresponding NOx as discussed above.



The percentage improvement in NOx and CO reduction is compared and it is observed that in new SCR system emissions are very closer to the Euro VI emission norms, which is highly beneficial for the proposed norms in India.



From the above comparison it is concluded that the distinct SCR system reduces the NOx emission.

VI. CONCLUSIONS

From the research study it can be concluded that

- Urea acts as a good catalyst for the NOx reduction in diesel engine.
- Due to Urea injection in New SCR system in the tail pipe **67.5%** NOx reduction has been achieved.
- Simultaneously CO also gets decreases.

- New SCR the most harmful gases are minimized and Pollution can be controlled. The vehicle performance will be enhanced.
- By using this SCR system in CI engine emission are nearer the EURO VI emission norms.

VII. REFERENCES

- [1] M. Koebel, M. Elsener and M. Kleemann, "Urea-SCR: a promising technique to reduce NOx emissions from automotive diesel engines", Elsevier catalysis today, (2000), Pg. 335-345.
- [2] Ioannis Gekas, Par Gabriel son and Keld Johansen, "Urea-SCR catalyst system selection for fuel and PM optimized engines and a demonstration of a novel urea injection system", Society of Automotive Engineers, (2002-01-0289).
- [3] Chun W. Lee and Ravi K. Srivastava, " Investigation of SCR impact on mercury speciation under simulated NOx emission control conditions ", Air & Waste Management Association, (2004), Pg. 1560-1566.
- [4] K. Chithambaramasari, N.V. Mahalakshmi and K. Jayachandran, "Application of SCR technique in NOx reduction of Diesel Engine Emission by Urea Injection Method", Canadian Journal on mechanical sciences & Engineering, (December 2011), Vol.2 No.8.
- [5] S. Gowthaman and K. Velmurugan, "Performance and Emission characteristics of direct injection diesel engine using Bio-diesel with SCR Technology", International Journal of Engineering Research and Applications, (October 2012), Vol.2 issue 5, Pg. 1083-1089.
- [6] S. Ghosh, Dr. S.N. Chaudhuri and D. Dutta, "Reduction of NOx emission by urea injection and marine ferromanganese nodule as SCR of diesel engine", International Journal of Engineering Research & Technology, (January 2013), Vol.2 issue 1.
- [7] Himangshu Sekhar Brahma and Dr.A. Veeresh Babu, "An experimental investigation on emission of neat Mahua biodiesel using urea-SCR", International Journal of Scientific & Technology Research, (August 2013), Vol.2 issue 8.
- [8] S. Ghosh, S.N. Chaudhuri and D. Dutta, " NOx reduction by using urea injection and marine ferromanganese nodule as SCR of a diesel engine fuelled with pongamia pinnata methyl ester ", International Journal of Modern Engineering Research, (April 2013), Vol.3 issue 2.
- [9] R. Praveen & S. natarajan, "Experimental study of selective catalytic reduction system on CI engine fuelled with diesel ethanol blend for NOx reduction with injection of urea solution" vol 6 No 2 Apr-May 2014 (ISSN: 0975-4024)
- [10] Xinmei Yuan & Hongqi Liu, Ying Gao "Diesel engine SCR control: Current development & future challenges - 2015(1:121-133)
- [11] Kleemann, M., Dissertation Nr. 13401, ETH Zurich, 1999.



- [12] H. Bosch, F. J. J. G. Janssen: "Catalytic Reduction of Nitrogen Oxides: A Review on the Fundamentals and Technology", *Catalysis Today*, 2(369), 1988.
- [13] Perry, R. A. And Siebers, D. L. Rapid reduction of nitrogen oxides in exhaust gas streams. *Nature*, 324, 1986,
- [14] Hug, H. T., Mayer, A., and Hartenstein, A., SAE Technical Paper Series, 930363, Detroit, March 1-5, (1993).
- [15] C.M.SCHAR, C.H. Onder and H.P. Geering, M Elsener, "Control of a Urea SCR catalytic Converter System for a Mobile Heavy Duty Diesel Engine", *SAE Transactions* 2003010776 (2003).
- [16] Chakravarthy, K., Choi, J.-S., and Daw, S. Modeling SCR on zeolite catalysts – A summary of observations on SCR kinetics based on the open literature. In Eighth DOE-CLEERS Workshop, Dearborn, Michigan, 17-19 May 2005.
- [17] Frickel, D.W., D'Addio, E., Lauterbach, J.A., Lobo, R.F., "The Ammonia Selective Catalytic Reduction Activity of Copper Exchanged Small Pore-zeolites", *App. Catal. B: Environmental*, 102, 441-448, 2011.
- [18] Koebel, M. and Strutz, E. O., "Thermal and Hydrolytic Decomposition of Urea for Automotive Selective Catalytic Reduction System: Thermo chemical and Practical Aspects," *Ind. Eng. Chem. Res.*, 42, 2093-2100, 2003.
- [19] Yim, S. D., Kim, S. J., Baik, J. H., Nam, I. S. et al., "Decomposition of Urea into NH₃ for the SCR Process," *Ind. Eng. Chem. Res.*, 43, 4856-4863, 2004.
- [20] Girard, J., Snow, R., Cavataio, G., and Lambert, C., "The Influence of Ammonia to NO_x Ratio on SCR Performance," SAE Technical Paper [2007-01-1581](#), 2007,
- [22] Hünnekes, E., van der Heijden, P., and Patchett, J., "Ammonia Oxidation Catalysts for Mobile SCR Systems," SAE Technical Paper [2006-01-0640](#), 2006,
- [23] Alano, E., Jean, E., Perrot, Y., Brunel, J. et al., "Compact SCR for Passenger Cars," SAE Technical Paper [2011-01-1318](#), 2011.
- [24] Tan, J., Solbrig, C., and Schmiege, S., "The Development of Advanced 2-Way SCR/DPF Systems to Meet Future Heavy-Duty Diesel Emissions," SAE Technical Paper [2011-01-1140](#), 2011.
- [25] Chatterjee, S., Conway, R., and Walker, A., "Emission Reduction in On-road Heavy Duty Diesel Applications with the Continuously Regenerating Technology (CRT®) Diesel Particulate Filter," SAE Technical Paper [2001-28-0049](#), 2001.
- [26] Walker, A., Allansson, R., Blakeman, P., Lavenius, M. et al., "The Development and Performance of the Compact SCR-Trap System: A 4-Way Diesel Emission Control System," SAE Technical Paper [2003-01-0778](#), 2003,
- [27] Sinya Sato et al, "The study of NO_x reduction using Urea- SCR system for a heavy-duty diesel engine", 20045293 Proceedings of JSAE Annual Congress (2004).
- [28] Satoshi Hiranuma et al, "Aftertreatment System for Commercial Diesel Engine (First Report), 20085359 Proceedings of JSAE Annual Congress (2008).
- [29] Minoru Kowada et al "Development of PM and NO_x Reduction Aftertreatment System for Heavy-Duty Commercial Vehicle, 20105725 Proceedings of JSAE Annual Congress (2010).
- [30] Hirose, S., Miyairi, Y., Katsube, F., Yuuki, K. et al., "Newly Developed Cordierite Honeycomb Substrate for SCR Coating Realizing System Compactness and Low Backpressure," SAE Technical Paper [2012-01-1079](#), 2012,
- [31] Fujii S., Hirose S., Sakamoto H. et al., "Potential of Advanced Substrate Technology for SCR Emission Control System", CTI4th International Conference, NO_x Reduction, Current and Future Solution for On- and Off-Road Applications.
- [32] Schaefer-Sindlinger A., Dinges T., Furuta Y. et al., "Latest Developments for Substrates and Filters in Heavy Duty Applications", SAE 2012 Heavy-Duty Diesel Emissions Control Symposium.
- [33] Kikuchi S., Hachio S., Okayama T., Inoue S. et al., "High Cell Density and Thin Wall Substrate for Higher Conversion Ratio Catalyst" 1999-01-0268.
- [34] Paule, M., Mackensen, A., Binz, R., and Enderle, C., "Challenges for the Next Generation of BlueTEC Emission Technology," SAE Technical Paper [2011-01-0294](#), 2011,
- [35] Hünnekes, E., van der Heijden, P., and Patchett, J., "Ammonia Oxidation Catalysts for Mobile SCR Systems," SAE Technical Paper [2006-01-0640](#), 2006
- [36] Alano, E., Jean, E., Perrot, Y., Brunel, J. et al., "Compact SCR for Passenger Cars," SAE Technical Paper [2011-01-1318](#),
- [37] Tan, J., Solbrig, C., and Schmiege, S., "The Development of Advanced 2-Way SCR/DPF Systems to Meet Future Heavy-Duty Diesel Emissions," SAE Technical Paper [2011-01-1140](#), 2011,
- [38] Kleemann, M., Elsener, M., Koebel, M., and Wokaun, A., "Hydrolysis of Isocyanic Acid on SCR Catalysts," *Ind. Eng. Chem. Res.*, 39, 4220-4126, 2000.
- [39] Lundstrom, A., Snelling, T., Morsing, P., Gabrielsson, P. et al., "Urea Decomposition and HNCO hydrolysis over Titanium Dioxide, Fe-Beta and γ -Alumina", *Applied Catalysis B: Environmental*, 106, 273-279, 2011

IJEAST

INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY

ABOUT IJEAST

International Journal of Engineering Applied Science and Technology (IJEAST) is a peer-reviewed, open access journal that publishes high-quality research papers in the field of Engineering, Applied Science and Technology.

IJEAST aims to provide a platform for researchers, academicians, and professionals to share their innovative ideas, research findings, and practical experiences with the global scientific community.

FOCUS AREAS

- Engineering
- Applied Science
- Technology
- Innovation & Development
- Interdisciplinary Studies



PEER REVIEWED

All submissions are rigorously peer reviewed to ensure quality.



OPEN ACCESS

Free and unrestricted access to research for all.



GLOBAL REACH

Connecting researchers and professionals worldwide.



TIMELY PUBLICATION

We ensure a swift and efficient publication process.



For more information, visit our website

www.ijeast.com



INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY

✉ editor@ijeast.com

🌐 www.ijeast.com

📍 India



2455-2143