



IJEAST

INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY



VOLUME : 6 ISSUE : 4 Print / Issue Publication Date: 17-Oct-2021



ISSN : 2455-2143



Indexed In



WWW.IJEAST.COM

editor@ijeast.com



PERSON RE-IDENTIFICATION USING DEEP METRIC LEARNING

Ms. Shruti Jalapur
Department of CSE

SECAB Institute Vijayapura, Karnataka, India

Ms. Bibi Ayesha Hundekar
Department of CSE

SECAB Institute Vijayapura, Karnataka, India

Abstract— Today everyone faces a multitude and variety of threats ranging from robbery, kidnapping and terrorism to murder. To avoid these threats, authorities need to collect real-time information about what's going on in and around the city. New technologies are therefore being developed to make cities safer and more risk-free. Here we have built a reliable system that recognizes the person from every angle from a recorded image. We can get the input into the systems through CCTV cameras installed in public places where these types of life threatening events take place. It is easy to install these cameras in public places, and it is easier to monitor and store the data. The developed system uses deep metric learning and the machine learning platform, Tensor Flow and Keras. It's a type of machine learning where the system iteratively performs calculations to know the patterns. The system processes recorded images and compares them with existing data records in order to identify the person. The comparison is made based on certain selected features. The results are more accurate (98.18%) compared to existing systems.

Keywords— Person Re-identification, Deep metric Learning, CNN

I. INTRODUCTION

An Introduction to Machine Learning: Machine learning is a branch of Artificial Intelligence (AI). For this reason, machine learning focuses on developing computer programs that can access and use data to learn on their own. Machine learning has been a buzzword for several years. Arthur Samuel, an American IBM researcher and pioneer in the field of computer games and artificial intelligence, coined the phrase machine learning in 1959. In 1997, Tom M. Mitchell published a widely referenced, more formal explanation of the machine learning algorithms: "In regard to a task T, a computer programme should learn from experience E. and quantify some performance."

Machine learning is a type of deep metric learning. Deep metric learning (DML) is a distance-metric learning paradigm that combines deep learning and metric learning. This requires that computer systems perform iteratively calculate to identify patterns themselves. This means after a deep learning computer recognize that an image it is evaluated

has the shape of a rectangle, oval or pattern by going through n cycles, and therefore our project will use the same logic as that Person re-identification applied via deep metric learning, in which it goes through n cycles to identify a person by assessing the similarities in relation to the data provided and finally presenting the positive results.

To make this possible, we use Torch, the pytorch-based library for deep metric learning, which is specifically considered for the identification of a person.

II. PROPOSED ALGORITHM

Implementation of this project is divided into three modules

1. Dataset preparation:

- Three classes are made namely a, b and c
- The class 'a' contains images of x person, class 'b' contains images of y person and class c contains images of 'z' person
- All the classes are trained with their respective images around a data of 1400 images are trained
- And a own dataset is created

2. Training the images:

- After collecting the database the next procedural step is to train the data
- This is a major act to gather the data by collecting the images and training at least for 1 hour for a good accuracy
- Duplicating the images hence for the better learning of the machine

3. Analyzing the data:

- In this step we analyse the data and try to match it out with the present database
- And once the needed picture matches with the given database the final output can be presented
- And hence the last step is the final decision of identifying a person

We used the transfer-learning technique, MobileNet with image net weights as the base model with frozen upper layers, we added new layers to the base model and refined them on our user-defined data set,

1. MobileNet is an image classification model, it is a neural network with dense convolutional layers and pooling / subsampling layers. Compared to other

similar image classification models / algorithms like vgg116, densenet, Xception, .. etcyolo gives better accuracy.

2. In combination with the mobilet image classification model, we added a few new levels and retrained it with new data adapted to our images. The accuracy when training the model was 99.6%
3. The new model can be used to process the image pixels as tensors flowing out of the top network layer and making the predictions
4. The model is then saved as model.h5 and model.json and can be loaded with load weights and used for predictions.
5. The saved model takes the paths of the images and converts them into corresponding pixel values and makes them available to the saved model with the function [model.predict].
6. We used opencv to read and display the input images from the system path. The output is specified as ["TRUE" / "FALSE"] values.

Transfer Learning (TL) is a machine learning (ML) research problem that well defined on the answer one issue and then apply that knowledge to a different but related problem. For example, learn to identify cars when they are used to identify knowledge trucks. Although the two areas of formal relationships are limited, this area of research has some references to the long history of the psychological literature on learning transfer. From a practical point of view, reinforcement learning resources are the recycling or transfer of information about learning tasks that are new to the task.

III. EXPERIMENT AND RESULT




figure 1: Beforedetection

This is a sample image that we nourish on the algorithm and expect our algorithm to determine and recognize the image and predict the output of this image, that is, identify whether it is the same person or not, in accordance with the appropriate class.




figure 2 After detection

Depending on your needs, our algorithm recognizes the image based on its classes and nominates the image based on its tag and determines the dimensions of the image.

Input kind :We also describe and analyze the File trail or pathway for a image, a numpy array, rather a File track or Stream for a image as an Input Image.

Output kind : We also describe for the "Detect Image FromImage" operation have to deliver the Image of the formation with file or a numpy array.

In this segment a complete experimental similarity of the different face recognition algorithms has been introduced. The numerous performance metrics for examining the results are accuracy, precision, detection rate, and false detection rate. Accuracy indicates the proportion of true results, both true and negative. The accuracy is recorded efficiently.

The experiment shows excellent results for the proposed algorithm. The low false detection rate indicates that the algorithm can distinguish between the actual skin color and background color with the appearance of the skin color. The recognition rate is 98.18%.




IV. CONCLUSION

This paper illustrates the process related to person re-identification. It uses deep metric learning for this same purpose. The Decorrelated Centralized Loss with Normalize-Scale algorithm provides an accuracy of 98.18%. This offers better efficiency compared to existing methods. This system is better suited for tracking down criminals in criminal matters such as robbery, terrorist attacks, intruder detection and much more. Its efficiency can be further increased by using tensorflow and keras as a library and module internet with its own organized data sets. This can be a new approach that can be implemented in the future.

V. REFERENCE

- [1] R. Layne, TM Hospedales and S. Gong, "Attributes-based re-identification", in Person Re-Identification Springer, 2014, pp. 93–117.
- [2] E. Ahmed, M. Jones and TK Marks, "An Improved Deep Learning Architecture for Person Re-Identification", in Proceedings of the Conference on Computer Vision and Pattern Recognition, 2015, pp. 3908-3916.
- [3] Liang Zheng, Hengheng Zhang, Shaoyan Sun, ManmohanChandraker, and QiTian, "Personre-identi ficationinthewild," in CVPR, 2017.
- [4] M. Farenzena, L. Bazzani, A. Perina, V. Murino and M. Cristani, "Person re-identi fication by symmetry-driven accumulation of local features", 2010 IEEE Computer Society Conference on Computer Vision and Pattern Recognition, 2010, pp. 2360-2367.
- [5] SakrapeePaisitkiangkrai, ChunhuaShen and Anton van den Hengel, "Learningtorankinpersonre-identi ficationwithmetric ensembles", in Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, 2015, pp. 1846–1855.
- [6] S. Liao, Y. Hu, X. Zhu and SZ Li, "Person reidenti fication by local maximum instance Representative and metric learning", in CVPR, 2015.
- [7] Bedagkar-Gala, A. and SK Shah, An overview of approaches and trends in person re-identification. Image and image processing, 2014. 32 (4): p. 270-286.
- [8] AlexKrizhevsky, IlyaSutskever and Geoffrey E. Hinton, "Imagenet classi fication with deep convolutional neural networks", in Advances in neural information processing systems, 2012, pp. 1097–1105.
- [9] YC Chen, WS Zheng, JH Lai and P. Yuen, "An Asymmetrical Distance Model for the Depiction of Cross-Sighting Features in Person Re-Identification", IEEE Transactions on Circuits and Systems for Video Technology, vol. PP, No. 99, pp. 1-1, 2016.
- [10] R. Kawai, Y. Makihara, C. Hua, H. Iwama and Y. Yagi, "Person reidenti fication using view-dependent score-level



Models are evaluated using a test data set. The trained test set consists of the three classes "a, b & c", which include images of 3 different peoples with different backgrounds, objects and different image views. As can be seen, the class distribution in these test data was the same as in the training data. We get this security to measure approx. Generalized performance of the model. The main use of our $I_q \otimes x_q$ projection (image q to embedding q) is to look up visually similar images. After comparing the images, the algorithm returns TRUE or FALSE. If the compared images are TRUE or equal (checking the path given to the images in the algorithm), TRUE is returned, if not, the result is returned as FALSE. The results of various experiments are discussed in this results and discussion section. The outcome describe the advance algorithms presents stronger contract for the other algorithms since we created our own datasets in this project. The results of the proposed algorithm are also used for applications such as pose and expression.



fusion of gait and color features", in IKSR, 2012, p. 2694 - 2697.

[11] D. Tao, Y. Guo, B. Yu, J. Pang and Z. Yu, "Deep Multi-View Feature Learning for Person Re-Identification", in IEEE Transactions on Circuits and Systems for Video Technology, vol. 28, No. 10, p. 26572666, 2018.

[12] H. Han, AK Jain, X. Chen, F. Wang and S. Shan, "Heterogeneous Face Attribute Estimate: A deep multi-task learning approach" IEEE Trans. Muster Anal. Do. Intellect., Vol. 40, no. 11, pp. 2597-2609, Nov. 2018.

IJEAST

INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY

ABOUT IJEAST

International Journal of Engineering Applied Science and Technology (IJEAST) is a peer-reviewed, open access journal that publishes high-quality research papers in the field of Engineering, Applied Science and Technology.

IJEAST aims to provide a platform for researchers, academicians, and professionals to share their innovative ideas, research findings, and practical experiences with the global scientific community.

FOCUS AREAS

- Engineering
- Applied Science
- Technology
- Innovation & Development
- Interdisciplinary Studies



PEER REVIEWED

All submissions are rigorously peer reviewed to ensure quality.



OPEN ACCESS

Free and unrestricted access to research for all.



GLOBAL REACH

Connecting researchers and professionals worldwide.



TIMELY PUBLICATION

We ensure a swift and efficient publication process.



For more information, visit our website

www.ijeast.com



INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY

✉ editor@ijeast.com

🌐 www.ijeast.com

📍 India



2455-2143