

RAILWAY TRACK CRACK DETECTION ROBOT

Arya A, Megha P, Shijila S, Sreelakshmy M, Dr. V. Balamurugan, Swetha C Department of Electronics and Communication, Ahalia School of Engineering and Technology, Palakkad, Kerala-678557

Abstract: Cracks in railway tracks can be a serious safety concern for Indian Railways, which has one of the largest railway networks in the world. Cracks can develop in railway tracks due to seasonal changes, which cause the tracks to contract and expand.Ourrailbot presents a railway track crack detection system utilizing Raspberry Pi and Arduino Uno for efficient monitoring of track integrity. The increasing frequency of railway accidents underscores the need for reliable detection methods to identify cracks and defects in railway infrastructure. Our system employs an array of sensors, including ultrasonic and IR sensors, connected to the Arduino Uno for realtime data collection. The Raspberry Pi processes this data, implementing machine learning algorithms to analyze patterns and detect anomalies indicative of potential cracks. The system is designed to provide immediate alerts, allowing for timely maintenance and reducing the risk of accidents. This innovative solution aims to enhance railway safety and operational efficiency, ensuring a more reliable transportation network.

Keywords: Railway Tracks, Crack Detection, Safety Concern, Indian Railways, Seasonal Changes, Track Integrity Railbot, Raspberry Pi, Arduino Uno

I. INTRODUCTION

The safety and integrity of railway infrastructure are paramount, especially for a vast network like Indian Railways, which operates one of the largest railway systems in the world. Cracks in railway tracks pose significant safety hazards, often exacerbated by seasonal fluctuations that cause the materials to contract and expand. As the frequency of railway accidents continues to rise, it is essential to adopt innovative and reliable methods for detecting cracks and defects in railway tracks.

To address this urgent need, we present a cutting-edge railway track crack detection system that leverages the capabilities of Raspberry Pi and Arduino Uno. This system is designed to monitor track integrity efficiently and continuously. By utilizing a combination of ultrasonic and infrared sensors, our system collects real-time data, which is then processed by the Raspberry Pi. Implementing advanced machine learning algorithms, the system analyzes data patterns to identify anomalies that may indicate potential cracks. The ultimate goal of this innovative solution is to enhance railway safety and operational efficiency. By providing immediate alerts for necessary maintenance, our system aims to reduce the risk of accidents and ensure a more reliable transportation network for passengers and goods alike.

II. PROPOSED ALGORITHM

The proposed algorithm outlines the steps for implementing a railway track crack detection system using Raspberry Pi and ROS2 (Robot Operating System 2). This integration facilitates modular design and communication between different components of the system.

A Initialization

Start the Raspberry Pi and initialize ROS2 environment. Set up nodes for each component (e.g., camera, ultrasonic sensors, vibration sensors).

B Sensor Configuration

Configure the cameras to capture images of the railway track. Set up ultrasonic and vibration sensors to monitor track conditions.

C Data Collection

Image Capture Node: Continuously capture images using the camera and publish them to a designated ROS2 topic. Sensor Monitoring Nodes: Collect data from ultrasonic and vibration sensors and publish the data to their respective ROS2 topics.

D Data Pre-Processing

Image Processing Node: Subscribe to the image topic, apply image enhancement techniques (e.g., filtering, contrast adjustment) to prepare for crack detection. Vibration Signal Processing Node: Subscribe to vibration data topic, apply filters to clean the data.

E Crack Detection

Image Analysis Node: Analyze pre-processed images to detect cracks using techniques like edge detection and contour analysis. Publish results to a crack detection topic.

Vibration Pattern Analysis Node: Analyze vibration data for irregular patterns indicative of structural issues.

F Data Analysis

• Severity Assessment Node: Evaluate the detected cracks' severity based on size and location. This node subscribes to the crack detection topic and publishes severity results.



• Location Identification: Determine the specific location of cracks on the railway track and include this information in the published data.

G Machine Learning Integration

Implement a machine learning node that uses a trained model to improve crack detection accuracy. This node can process images and provide feedback on detection reliability.

H Alert Generation

Alert System Node: Subscribe to the severity assessment topic. Upon detecting a crack above a certain severity threshold, generate alerts (SMS, email, or local display).



Fig. 1. Railbot algorithm flow

III. EXPERIMENT AND RESULT

Integrating a PID controller with ultrasonic sensors allows for precise motor speed control in robotics, enabling effective obstacle avoidance and safe distance maintenance. By finetuning PID parameters, the system achieves responsive performance, enhancing robotic navigation in dynamic environments.

A System Integration

Combines PID controller with ultrasonic sensors for precise motor speed control based on distance measurements.

B Components Required

- Tinker cad Account: For circuit simulation.
- DC Motor: For movement.
- Ultrasonic Sensor: Measures distance.
- Microcontroller: Processes inputs and controls outputs.

- Motor Driver: Controls motor speed and direction.
- PID Algorithm: Consists of Proportional, Integral, and Derivative components, addressing current, past, and future errors.
- Motor Control: The microcontroller sends signals to the motor driver based on PID calculations, allowing smooth control.

C Implementation Steps

- Set up the circuit.
- Write code for sensor initialization and PID logic.
- Test and adjust PID parameters for optimal performance.

D Results

Fine-tuning PID parameters leads to responsive and accurate distance maintenance, enhancing robotic capabilities in dynamic environments







Fig. 2. Tinkercad PID Controller





Fig. 5. Joint State Publisher controlling URDF

E Robot Visualization Launch File

A configuration file was set up to start a visualization environment. This allows users to see the robot model in a

graphical interface, often using tools like Rviz. This made it easier to understand how the robot looks and works physically.

F GAZEBO Simulation Launch File

A launch file was developed for Gazebo, a robotics simulator that facilitates the testing of robotic algorithms within a 3D environment. This simulation offers realistic physics and sensor feedback, which are crucial for validating robotic behaviors in a controlled environment

G Control Algorithms Development

- Simple Controller: A basic control algorithm was implemented, managing the robot's movements through direct input-output relationships, without complex decision-making processes.
- Differential Drive Controller: Designed specifically for robots with a differential drive mechanism. Enables navigation by adjusting wheel speeds independently.
- Noisy Controller: In order to ensure more stable and dependable robot behavior while in operation, this controller was created to control and correct for noise in sensor data or actuator performance.



Fig. 6. Simple Controller

er controller/ord set genetry mag/anithanithenithenithet.comm.ed real table of peritonet with the set of the s		1 • 2 d + mm - 2
<pre>er_controller/ord_vel_gesretry_mags/anithanithanithesi-frames_esf res2 tasic pub /r wem_controller/ord_vel_gesretry_mags/anithanithanithesi-frames_esf res2 tasic pub /r anithgeninbot:=/rame_vef res2 tasic pub /rever_controller/ord_vel_gesretry_mags/mag/ bitsStarped "NewBer:ader:ader: starp: 8c = starp: 8c = frame_lbi '' tasisisr0 lineari0 st 8.8 y: 8.8 y: 8.8 z: 8.8 argular: st 2.4 y: 8.8 y:</pre>	adaptitie (see al	
en_controller/ond_sel_geometry_maps/onithignetibioni-framem_end_real tapic pob (r aven_controller/ond_sel_geometry_maps/onithignetibioni-framem_esantibipartibioni-mithignetibueth antihignetibioni-framem_esa5 real topic pub framem_controller/ond_wel_geometry_maps/mags tets:Storped "Beader:ader: starge: Bc: 0 sect Ect 0 frame_id: " delation:0 frame_id: " delation:0 st.8.8 y: 0.8 z: 0.8 y: 0.8 z: 0.8 y: 0.8 z: 0.8 y: 0.4 y: 0.4 y: 0.4		NAME AND A DOCUMENT OF TAXABLE PARTY.
blag: 8c; 8 tag: 8c; 8 fraw_16; 1 tagitis:0 timerid s: 8,8 y: 8,8 y: 9,8 s: 9,8 timerid s: 8,8 timerid s:	er controller/ord sel gesetry regn/ani aven controller/ord sel geomitianithian anitiganithiot:-/reven_es5 res2 tooic a Diartitiered "heater aler ofer	thearithearithearithearithearithearithearithearithearith thint:/rawa_wintHearithearithearithearithearith W /rawa_controller/cnd_wel_geometry_megs/meg/
Lingt Sc. 0 Introduct 0 fram_Lit: totstimu Lingt 10 st 8.8 yt 8.8 tr 9.8 monitor: st 9.8 tr 9	resolution and a second same same s	
10(1 %): 0 franc_(d; '' bild(1:ar)0 1)franc_(d; ar) s: 0.8 y: 0.8 y: 0.8 r: 0.8 r: 0.8 y: 0.4 y: 0.4	STORET BUT B	
* consistent # frame_lid: *** telestiant# linearif@ st 0.8 yt 0.8 argelant et 0.8 yt 0.8 r 0.8 r 0.8	1001 001 0	
Franz,Us: telstiart0 telstiart0 tr 0.0 r: 0.0 r: 0.0 r: 0.0 r: 0.0 r: 0.0 r: 0.0	handsac: W	
24142133710 11mm710 x1 8.8 y1 8.8 y1 8.8 mgs12x1 mgs12x1 x2 9.8 y1 9.8 y1 9.8 y1 9.8	Trave_Ltt:	
11mm;10 x: 0.8 y: 0.8 2: 0.8 abgn1x: x: 0.0 y: 0.8 y: 0.8 y: 0.8	twistiant8	
42 8.8 yr: 8.8 avgilar: e: 9.8 yr: 9.8	Tiresrid	
y: 0.8 I: 0.8 Mys14a: K: 0.8 V: 0.8 V: 0.8 V: 0.8	#1.8.8	
21 9.8 Mgalar: K: 9.9 Y: 9.9 Y: 9.9	yr. 8.8	
angular: 8: 0.0 y: 0.0 H: 0.0" > 1.0	z: 0.0	
に (0.0) (1) (0.0) (1) (0.0)	aveilart	
yr 9.4	ar 0.0	
21.9.5" - 10	V: 9.8	
	21 8.5" - 10	

Fig. 7. Differential Drive Controller

IV. CONCLUSION

The railway track crack detection system developed using Raspberry Pi and Arduino Uno represents a significant advancement in the maintenance and safety of one of the world's largest railway networks. By leveraging an array of sensors, including ultrasonic and IR sensors, the system effectively monitors track integrity in real-time, addressing the critical issue of crack formation due to seasonal changes. The integration of machine learning algorithms allows for accurate analysis and identification of anomalies, ensuring timely alerts are generated for maintenance teams.

This proactive approach not only enhances the safety of railway operations but also minimizes the risk of accidents, thereby safeguarding the lives of passengers and improving overall operational efficiency. The innovative design of this railbot lays the groundwork for future advancements in railway monitoring technology, ultimately contributing to a more reliable and secure transportation network for Indian Railways. By implementing such advanced detection methods, we can ensure the longevity and safety of railway infrastructure, paving the way for safer travel experiences.

V. REFERENCES

- S. Sureshkumar, C. Agash, (2021), "Augmented Reality with Internet of Things," ieeexplore.ieee.org, [Online].Available:https://ieeexplore.ieee.org/abstract /document/9395941/
- [2]. N. Mahfuz, O. Dhali, (2017), "Autonomous railway crack detector robot for bangladesh: SCANOBOT," ieeexplore.ieee.org, Accessed: Jul. 26, 2022.
 [Online]. Available: https://ieeexplore.ieee.org/abstract/document/828901
 4/
- [3]. M. Singh, S. Singh, J. Jaiswal, and T Hempshall,(2006) "Autonomous Rail Track Inspection using Vision Based System," in Computational Intelligence for Homeland Security and Personal Safety, Proceedings of the 2006 IEEE International Conference on,
- [4]. F. R. L. Boylestad and L. Nashelsky,(2012) "railway crack detection using gpa technology", 9th edition, Prentice Hall, USA, pp. 196-199.

[5]. A.Muley, S. Patil, A. S.- vol, and undefined (2017), "Railway track crack detection based on GSM technique," academia.edu,[Online].Available:https://www.acade mia.edu/download/51881200/IRJEV4I1222.

- [6]. Prof.P. Navaraja.(2014) "Crack Detection System For Railway Track By Using Ultrasonic and PIR Sensor" ISSN 2348-9928 International Journal of Advanced Informantion and Communication Technology Volume- 1, Issue-1
- [7]. J. N. L. A, L. Narayanan C, K. M. S, R. S and K. R,(2022),"Railway Track Crack and Key Detection





Robot using IoT,"International Conference on Edge Computing and Applications (ICECAA), pp. 623-628, doi:10.1109/ICECAA55415.2022.9936435.

- [8]. A. Muley, S. Patil, A. S., (2022), "Railway track crack detection based on GSM technique," https://www.academia.edu/download/51881200/IRJE TV4I1222.pdf
- [9]. M. Vemula, S. Dawn, A. Machagiri, S. L. Potipireddi and B. R. Bobbili,(2023) "Fault Detection in Railway Track using GSM And GPS System," 7th International Conference on Trends in Electronics and Informatics (ICOEI),pp.259-264,
- [10]. doi: 10.1109/ICOEI56765.2023.10125887.
- [11]. P. Lad and M. Pawar,(2016) "Evolution of railway track crack detection system,"2nd IEEE International Symposium on Robotics and Manufacturing Automation (ROMA),pp. 1-6 doi: 10.1109/ROMA.2016.7847816.
- S. P. Priya, P. S. Abarna, C. M. Devi, S. S. Hammed, M. P. Karthikeyan and K. M. Saravanan,(2024) "Track Damage And Obstacle Detection Using Multi Sensor Fusion Framework,"15th International Conference on Computing Communication and Networking Technologies (ICCCNT),pp.1-7, doi: 10.1109/ICCCNT61001.2024.10724817.
- [13]. A.A. Raj, C. K. V and R. G,(2023) "Robost Railway Crack Detection Scheme Using IR Sensor," International Conference on System, Computation, Automation and Networking (ICSCAN),pp. 1-5,doi: 10.1109/ICSCAN58655.2023.10395521.
- [14]. A.N. Suhas, S. Bhagavat, V. Vimalanand and P. Suresh,(2018),"Wireless Sensor Networks Based Monitoring of Railway Tracks,"International CET Conference on Control, Communication, and Computing (IC4),pp. 187-192, doi: 10.1109/CETIC4.2018.8531029.
- [15]. P. Kumar (2023), "A Review on Automatic Protection System and Risk Mitigation in Railways,"5th International Conference on Advances in Computing, Communication Control and Networking (ICAC3N), pp. 1653-1659, doi: 10.1109/ICAC3N60023.2023.10541341.